



*Installation and Verification of a Vertical
Hydraulically Fractured ZVI PRB in a
Residential Setting*

*Seventh International Conference on Remediation of
Chlorinated and Recalcitrant Compounds*

**Jim Ortman, Kevin D. Dyson, P.E., Peter J. Palko, CHMM, P.E., - Geosierra
Brian Bjorklund, P.G., Arun Chemburker, P.E. – ERM West, Inc.**

Medford, NJ - Alpharetta, GA

www.geosierraenv.com


Presentation Overview

- **Introduction**
- **Site Description/History**
- **Background Design Summary**
- **ZVI-PRB Installation**
- **Geometry, Thickness and Conductivity Verification**
- **Monitoring Results**

Introduction

- Geosierra Environmental, Inc. formed in 2007 following purchase of Geosierra, LLC. assets and licensing rights
- Exclusive North America License holder for 4 hydraulic fracturing and geophysical monitoring patents
- Hydraulic Fracturing implemented at seventeen (17) total pilot and full-scale ZVI PRBs from 15' to 115' bgs to virtually any depth
- Vertical hydraulic fracturing can be used to install from 3-inch to 9-inch thick pure iron PRBs
- Active resistivity real time monitoring used to ensure lateral fracture geometry

Introduction (cont'd)



Introduction (cont'd)

- ZVI degrades chlorinated ethenes through sequential dechlorination
- ZVI source is recycled engine block tailings
- Delivered in 3,000 lb supersacks
- Injected within cross linked food grade guar
- Enzymes breakdown gel with 1 – 3 hours leaving pure ZVI perpendicular to groundwater flow
- Degradation of sugars and starches by indigenous microbes immediately starts dechlorination process

Introduction (cont'd)

- “Green technology” benefits include:
 - Utilizes waste from engine block manufacturing
 - No external power sources (e.g. grid power) used to install the ZVI PRB
 - Utilizes self generating power unit with ULSD fuels and mineral oil based hydraulic oil
 - No ongoing operations and maintenance
 - No groundwater extraction and disposal
 - No ongoing power consumption
 - Land surface can be reclaimed



Site Description and History

- Former manufacturing facility that utilized TCE for degreasing operations
- Groundwater plume in two major distinct lithologic units (A and B Zones):
 - A1-Zone from 15' bgs to ~25' bgs (targeted zone for PRB)
 - Consists of clay, silty clay, clayey silt and silt
 - Hydraulic conductivity ranges from 0.62 – 11.5 ft/day
 - A2-Zone from 25 to ~50' bgs (targeted zone for PRB)
 - Consists of clay, silty clay, clayey silt and silt with interbedded lenses of coarse grained sand zones
 - Hydraulic conductivity ranging from 10.5 – 65.3 ft/day
 - Hydraulic gradients ranging from 0.001 – 0.004 ft/ft
 - B-Zone from 50' bgs to 80' bgs (treatment via source ISCO)
 - ◆ Consists of silty sand, sand, sandy gravel or gravelly sand
 - ◆ Hydraulic conductivity significantly higher than A-Zone


Site Description and History (cont'd)

- Dissolved phase groundwater plume flowing beneath local park and under residences
- Current vapor intrusion system installed within residential crawl spaces to reduce indoor air quality issues
- High traffic area including intersection that handles traffic flow to local elementary school
- Upgradient chemical oxidation ongoing to eliminate source area contamination




Site Description and History (cont'd)

- Site plan showing iso-concentration contours:



Background Design Summary


- Baseline column study used to determine site specific half lives
- Pre-PRB Installation Hydraulic Pulse Interference Testing across planned PRB location



Background Design Summary (cont'd)

- Complete MIP survey conducted by ERM along PRB alignment
- Probabilistic design utilizing twenty-five (25) Monte-Carlo simulation scenarios for numerous recent and historic data and geologic parameters
- Newly published multi-component reactive transport model used to evaluate mineral reactivity on iron surfaces
- Multi component model also evaluated life expectancy of ZVI PRB to 30-year life cycle inclusive of effects of inorganic passivation
- Based on the plume dimensions, detailed hydrogeologic assessments and various modeling scenarios, the ZVI-PRB was designed as follows:
 - 480-linear feet (l.f.) in total length, 455 tons of iron from 15 – 48' bgs
 - The core was designed as 4.5-inch thickness over 300-l.f.
 - The boundaries were 3-inch on either end over 180-l.f. length

Background Design Summary (cont'd)





ZVI-PRB Installation

- Installation of frac wells consisting of two (2) frac casings per well at 40-locations (resistivity receivers located under cones)



ZVI-PRB Installation (cont'd)

- Injections occur through frac wells that dilate under pressure to allow migration of cross linked iron gel vertically into the formation.




ZVI-PRB Installation (cont'd)

- Injections through custom mixing, blending and pumping systems




ZVI-PRB Installation (cont'd)

- Frac wells installed via mud rotary and hollow stem auger
- Injection and monitoring equipment, injection gels, enzymes and iron mobilized to the site
- Remote mixing system facilitates mixing of gel and transfer to pumping system
- Gel mix QA/QC parameters including
 - pH – 4 – 5 s.u. to enhance enzyme destruction of cross-linked guar
 - Viscosity – high enough to suspend iron without settling
 - Resistivity – substantial contrast against background soil resistivity to monitor frac propagation with active resistivity system







Geometry, Thickness and Conductivity Verification


- Real time fracture monitoring through active resistivity system
- Resistivity receivers installed on 20-foot centers
- Low voltage, 97 hz square wave charges the casing and excites the gel/iron mixture during fracturing
- Propagation of the excited iron through the formation is logged by the downhole receivers and reduced via inverse algorithms to images
- Fracture geometry is used to verify coalescence of the wall from end to end



Geometry, Thickness and Conductivity Verification (cont'd)



Geometry, Thickness and Conductivity Verification (cont'd)



Geometry, Thickness and Conductivity Verification (cont'd)


- Following completion of installation, thickness verification completed with inclined profile borings thru PRB
- Utilized Geoprobe and Sonic Drilling methods
- Attempts to minimize disturbance during installation of 2-inch PVC casing through PRB and collect intact core
- Following installation of casing, insert 3-axis magnetometer and collect readings before, within and following exit of PRB
- Multiple runs up and down casing measures the low level magnetic field generated by the iron PRB




Geometry, Thickness and Conductivity Verification (cont'd)

- Verification of installation per the design specifications was completed using the inclined profile boring and magnetometer:

Deep PRB Section



Shallow PRB Section (note secondary fractures from Deep PRB Section)



Geometry, Thickness and Conductivity Verification (cont'd)

- Following installation, the post-PRB installation Hydraulic Pulse Interference Test was re-run on the same wells from the previous test to confirm the PRB has no impact on groundwater flow




Table 7. Summary of Hydraulic Pulse Interference Test Results. [REDACTED] ZVI PRB. [REDACTED] California.

G205001

Test Location	Pre-PRB Installation Hydraulic Pulse Interference Testing			Post-PRB Installation Hydraulic Pulse Interference Testing			Percent Change Pre Post
	Hydraulic Conductivity (ft/day)	Hydraulic Conductivity (cm/sec)	Storativity (1/ft)	Hydraulic Conductivity (ft/day)	Hydraulic Conductivity (cm/sec)	Storativity (1/ft)	
Pulse Test Data Summary							
Shallow Well Pairs							
Source Well MW31A; Receiver Well MW30A	11.5	4.06E-03	1.17E-04	15.3	5.40E-03	1.17E-04	33%
Source Well MW31A; Receiver Well MW32A	0.615	2.17E-04	1.43E-05	1.09	3.83E-04	1.43E-05	77%
Shallow Wells Average Conductivity	6.06	2.14E-03	6.57E-05	8.20	2.89E-03	6.57E-05	36%
Shallow Wells Geometric Mean Conductivity	2.66	9.38E-04	4.09E-05	4.08	1.44E-03	4.09E-05	54%
Shallow Wells Standard Deviation from Mean	7.70	2.72E-03	7.26E-05	10.95	3.54E-03	7.26E-05	31%
Deep Well Pairs							
Source Well MW31A2; Receiver Well MW30A2	10.5	3.70E-03	2.17E-04	10.9	3.85E-03	2.17E-04	4%
Source Well MW33A2; Receiver Well MW32A2	65.3	2.30E-02	2.04E-04	64.2	2.26E-02	2.04E-04	-2%
Deep Wells Average Conductivity	37.90	1.34E-02	2.11E-04	37.55	1.32E-02	2.11E-04	-1%
Deep Wells Geometric Mean Conductivity	26.18	9.24E-03	2.10E-04	26.45	9.33E-03	2.10E-04	1%
Deep Wells Standard Deviation from Mean	38.75	1.37E-02	9.19E-06	37.69	1.33E-02	9.19E-06	-3%
Combined Well Pairs							
Source Well MW31A; Receiver Well MW30A2	32.9	1.16E-02	7.08E-05	50.3	1.77E-02	7.08E-05	53%
Source Well MW31A2; Receiver Well MW30A	22.9	8.08E-03	2.23E-04	19.0	6.70E-03	2.23E-04	-17%
Source Well MW33A; Receiver Well MW32A	16.5	5.82E-03	3.17E-05	24.8	8.75E-03	3.17E-05	50%
Source Well MW33A2; Receiver Well MW32A	54.8	1.93E-02	3.26E-05	52.3	1.85E-02	3.26E-05	-5%
Combined Wells Average Conductivity	31.78	1.12E-02	8.95E-05	36.60	1.29E-02	8.95E-05	15%
Combined Wells Geometric Mean Conductivity	28.73	1.01E-02	6.36E-05	33.37	1.18E-02	6.36E-05	16%
Combined Wells Standard Deviation from Mean	18.77	5.92E-03	9.08E-05	17.18	6.05E-03	9.08E-05	2%


GEOSIERRA ENVIRONMENTAL, INC.

Table 7 - Pre - Post HPIT Results Summary

Summary of Results


- A total of 465 Tons of ZVI were emplaced to build a 480-foot long, 33-foot tall ZVI-PRB
- Installation was completed in approximately 4-months with little impact on residences and local traffic conditions
- Following ZVI-PRB construction, ERM installed monitoring wells immediately up and downgradient to monitor influent and effluent water quality and CVOC trends
- A total of eight (8) pairs were installed between 4 and 10 feet up and downgradient
- To date reduction of CVOCs through the PRB range from 88% to 97% in 7 of 8 monitoring wells with downward trends in the 8th well
- Groundwater enters the PRB between 50 and 500 PPB and exits at less than the MCL for TCE in 6 of 8 monitoring wells with the remaining two wells quickly approaching MCLs

Summary of Results



Summary of Results

➤ Cross section of sampling results



Thank You!

- We would like to thank the ERM, West, Inc. crew of Brian Bjorklund, Arun Chemburkar, John Moe and others for supporting this project!